



MODEL NUMBER: 5410-A2 Allen Occasional Chair

DIMENSIONS w25 d27 h37.5
ah 26.5 sh 20.5 sd 20 iw 18

SEAT CUSHION: Tight Seat

HR-40 DAC Soy-based polyurethane with a poly Dacron wrap. 2.75 pounds per cubic foot density foam with a 40 IFD (Indentation Force Deflection). Soy-based cushions are sustainable, and renewable. All Fairfield foam cushions meets CAL 117-2013.

SEAT SUPPORT: 8.5 gauge No-Sag™ sinuous springs attached with No-Sag™ squeak-proof clips.

BACK CUSHION: Tight Back

Tight back cushions are Soy-based polyurethane with a poly Dacron wrap. 1.0-1.5 pounds per cubic foot density foam with a 17-35 IFD (Indentation Force Deflection), with a .75 oz. Dacron topper. Soy-based cushions are sustainable, and renewable. All Fairfield foam cushions meets CAL 117-2013.

BACK SUPPORT: Heavy duty FLW propex with Insul Pad to give proper shape and support.

FRAME: Solid kiln dried hardwoods and engineered laminated hardwood veneers. Solids are harvested from certified sustainable U.S. forest. Plywood is compliant with California Resource Board (CAEB) 93120 phase 2, formaldehyde emissions requirements of the Airborne Toxic Control Measure (ATCM)

FRAME DESCRIPTION: Frames are engineered to use a variety of joint construction. Triple dowel construction is standard. Many major stress joints feature both triple doweling, mortise and tenon and corner blocks that are attached with PVAC glue, lag bolts, stables and four screws. Frames are laboratory tested to BIFMA approved standards and have a weight capacity of 300 pounds.

GLIDES: A selection of 12 glides are available as an option.

FINISH: Fairfield offers 2 finishes: Standard-9 Step pre-catalyzed nitrocellulose finish available in multiple colors. Fair-Shield Plus- 7 step conversion varnish that offers enhanced chemical, moisture, mar and scratch resistances, ideal for high-use commercial environments. Both finishes feature Silver-Ion technology that inhibits the growth of mold, mildew fungus and bacteria and both are formulated with UV inhibitors to reduce harmful effects of sunlight. Fair-Shield Plus can be cleaned with a 5% bleach solution provided the wood is rinsed after cleaning.

UPHOLSTERY: Multi-fabric combinations available with welting. Nailhead trim standard as shown.

WARRANTY: Fairfield warrants its merchandise to be free of defects in materials and workmanship for Five (5) years under normal single shift use and conditions to the original purchaser. See the price list for exceptions. Textiles are covered under separate warranty by the textile supplier.

