



MODEL NUMBER: C-1833-50 Danville Sofa

DIMENSIONS w82 d33.5 h36
ah 30 sh 20.5 sd 21.5 iw 69

SEAT CUSHION: Loose Cushion

SUPPORT PLUS 3L Soy-based all foam™ cushion. The core is a firm compression of 2.5 density with a 28 (plus or minus) IFD Indentation Force Deflection, wrapped on each side with a layer of medium compression foam. The cushion is encased in a white non-woven ticking. The outer layer provides a softer initial feel, while the inner core provides the firm support. This Premium cushion is designed for high shape retention and will resist fatigue and sagging. It is especially recommended for use in Commercial/Contract applications. All Fairfield foam cushions meets CAL 117-2013.

SEAT SUPPORT: 8.5 gauge No-Sag™ sinuous springs attached with No-Sag™ squeak-proof clips.

BACK CUSHION: Tight Back

Tight back cushions are Soy-based polyurethane with a poly Dacron wrap. 1.0-1.5 pounds per cubic foot density foam with a 17-35 IFD (Indentation Force Deflection), with a .75 oz. Dacron topper. Soy-based cushions are sustainable, and renewable. All Fairfield foam cushions meets CAL 117-2013.

BACK SUPPORT: 11 Gauge No-Sag™ sinuous springs with "squeak-proof" clips covered with a poly-woven fiber to give proper shape and support.

FRAME: Solid kiln dried hardwoods and engineered laminated hardwood veneers. Solids are harvested from certified sustainable U.S. forest. Plywood is compliant with California Resource Board (CAEB) 93120 phase 2, formaldehyde emissions requirements of the Airborne Toxic Control Measure (ATCM)

FRAME DESCRIPTION: Frames are engineered to use a variety of joint construction. Triple dowel construction is standard. Many major stress joints feature both triple doweling, mortise and tenon and corner blocks that are attached with PVAC glue, lag bolts, stables and four screws. Frames are laboratory tested to BIFMA approved standards and have a weight capacity of 300 pounds.

GLIDES: A selection of 12 glides are available as an option.

FINISH: Fairfield offers 2 finishes: Standard-9 Step pre-catalyzed nitrocellulose finish available in multiple colors. Fair-Shield Plus- 7 step conversion varnish that offers enhanced chemical, moisture, mar and scratch resistances, ideal for high-use commercial environments. Both finishes feature Silver-Ion technology that inhibits the growth of mold, mildew fungus and bacteria and both are formulated with UV inhibitors to reduce harmful effects of sunlight. Fair-Shield Plus can be cleaned with a 5% bleach solution provided the wood is rinsed after cleaning.

UPHOLSTERY: Multi-fabric combinations available with welting. Nail head trim available on the base and arms as an option.

WARRANTY: Fairfield warrants its merchandise to be free of defects in materials and workmanship for Five (5) years under normal single shift use and conditions to the original purchaser. See the price list for exceptions. Textiles are covered under separate warranty by the textile supplier.